

**FEATURES:**

- Functions W30,HV,HA, Phase sequence, Audible continuity test.
- Active, Reactive, Apparent power on.
- Phase sequence with one wire.
- Single / Three phase systems.
- Active, Reactive, Apparent energy on Power, Factor,  $\cos\theta$  on Single.
- Three phase systems.
- MAX / MINI / AVG function.
- Fast Peak function. (1ms)
- Voltage I Current Harmonics up to 25th with THD %.
- Energy.
- Total Harmonic Distortion.(HTD%).



## **SPECIFICATIONS:**

- Auto range.
- Auto power Off.
- Data hold.
- Dimension :205x64x39 mm. (LxWxH)
- Weight : 280g. (Including battery)
- Power : 2 batteries 1.5V AAA type.
- Continuity buzzer.( $<400$ )
- Frequency.
- Peak hold.

<b>Max measuring current</b>	400A
<b>Display counts</b>	10000 Count Backlit LCD
<b>Max conductor size</b>	30mm (11.8")
<b>AC Current</b>	0.1A~400A $\pm$ (1.0% +3)
<b>AC Voltage</b>	0.1~599.9V $\pm$ (1.0%+3)
<b>DC Voltage</b>	0.1~599.9V $\pm$ (1.0%+3)
<b>Resistance</b>	0.1 $\Omega$ ~1.99.9 $\Omega$ $\pm$ (1.0%+5)



21 Toh Guan Road East,  
#09-01, Toh Guan Centre,  
Singapore 608609.

[sales@qsafe.com.sg](mailto:sales@qsafe.com.sg)

[www.qsafe.com.sg](http://www.qsafe.com.sg)

+65 8123 4812

