

FEATURES:

- CAT IV 600V
- LCD Backlit Display, with maximum reading of 3999.
- Analog Bargraph Display
- True Rms.
- AC voltage range: 0 to 1000V.
- DC voltage range: 0 to 1000V.
- AC Current range: 0.1 μ A to 10A.
- DC Current range: 0.1 μ A to 10A.
- Auto power off (15 minutes).
- Min/Max.
- ACV, DCV, ACA, DCA, Resistance, Diode, Frequency, Capacitance, Duty Cycle, Continuity.
- Range Hold.
- Data Hold.
- REL.
- Accessories.



SPECIFICATIONS:

Overvoltage Category	CAT IV 600V CAT III 1000V
LCD	3999 counts
Sampling rate	2.5/S
Backlit	YES
Bargraph	YES
DC Voltage	0.1mV~ 1000V(0.5%+2)
AC Voltage	0.1V~750V(1.3%+5)
DC Current	0.1uA~10A(1.0%+3)
AC Current	0.1uA~10A(1.5%+5)
Resistance	400Ω, 4k, 40k, 400k, 4M,40MΩ
Accuracy	±1(1.0% + 2)
Protection	1000Vrms
Continuity Buzzer	YES
Diode Test	YES
Frequency	1Hz~100KHz
Capacitance	4n, 40n, 400n, 4u, 40u, 400u, 4m, 40mF
Accuracy	±1(1% + 5)
Temperature	-40~800°C -40°F~1382°F
Accuracy	°C(±2%+3) °F(±2%+5)
Max	Max/Min
Accessories : Carrying case, test leads, manual, battery	* T10 Temp adapter



sales@qsafe.com.sg

www.qsafe.com.sg

+65 8123 4812

21 Toh Guan Road East,
#09-01, Toh Guan Centre,
Singapore 608609.

