

FEATURES:

- 3 3/4 digits LCD with backlit and analog bar graph.
- Test range :ACA, DCA, ACV, DCV, x10RPM, Ω , Continuity, Diode and Frequency.
- Double injection outer case

FUNCTIONS:

- Continuity buzzer.(<40 Ω)
- Overload indication.
- Low battery indication.
- Auto range.
- Auto power off (30 minutes).
- (D-H) data hold.
- Power supply : 2 batteries 1.5V AAA type.
- Dimension : 205x64x39mm. (LxWxH)
- Weight :280g.
- Diode.



SPECIFICATIONS:

Max measuring current	400A
Display counts	4000
Max conductor size	30 mm
AC Current	0.01A~400A $\pm(2.0\%+10)$
DC Current	0.01A~400A $\pm(2.0\%+10)$
AC Voltage	0.1mV~600V $\pm(1.0\%+3)$
DC Voltage	0.1mV~600V $\pm(0.8\%+2)$
X10RPM	0~1200 x10RPM ($\pm 2.0\%+4d$)
Resistance	0.1 Ω ~40M Ω $\pm(1.0\%+3)$
Frequency	1Hz~100KHz $\pm(0.8+3)$



21 Toh Guan Road East,
#09-01, Toh Guan Centre,
Singapore 608609.

sales@qsafe.com.sg

www.qsafe.com.sg

+65 8123 4812

