

FEATURES:

- 3 3/4 digits LCD with backlit and analog bar graph.
- Test range : ACA, ACV, DCV, Ω , Continuity, Frequency and Diode.
- Double injection outer case.

FUNCTIONS:

- Continuity buzzer.($<40\Omega$)
- Overload indication.
- CAT III
- Low battery indication.
- Auto range.
- Auto power off. (30 minutes)
- D-H : data hold.
- $\Omega / \text{ continuity }$ selection button for the composite functions of Ω / Continuity.
- MAX / MIN.
- Power supply.
- Dimension : 205x64x39 mm.(LxWxH).
- Weight : About 280g. (Including battery)



SPECIFICATIONS:

Max measuring current	400A
Display counts	4000 Count
Max conductor size	30mm (11.8")
AC Current	0.01A~400A $\pm$ (2.0% +10)
AC Voltage	1mV~600V $\pm$ (0.8%+2)
DC Voltage	1mV~600V $\pm$ (1.0%+3)
Resistance	0.1 Ω ~40M Ω $\pm$ (1.0%+3)
Frequency	Yes



sales@qsafe.com.sg

www.qsafe.com.sg

+65 8123 4812

21 Toh Guan Road East,
#09-01, Toh Guan Centre,
Singapore 608609.

