

Large LED Screen CO2 / Temperature / Humidity Monitor

Specifications :

CO2 Test Range	0~9999 ppm	Humidity Test Range	5% ~ 95% RH
Accuracy	±70ppm or ±5% of reading (0~2000ppm) whichever is greater over 2000ppm ±7%	Accuracy	±3% RH(20% ~ 80% RH@25°C ±5% RH(20% >80%@25°C
Resolution	1ppm	Update time	1 time / second
Temp test range	-20°C~70°C / -4°F~158°F	Weight	1000g
Accuracy	±1°C(0°C~40°C / 32°F~104°F) ; Other ±2°C/±3.6°F	LED Display	214x120mm(8.4x4.73 inch)
Resolution	0.1°C / 0.1°F (0~35°C / 32°F~95°F); other 1°C / 1°F	Power	AC/DC Adapter (9V~12V / 1A)

Model	CO2	Temperature	Humidity	30000 Records	Clock
TM-187D (with DG-186)	●	●	●	●	●

Applications:

- Warehouses
- Chambers / incubators
- Laboratories
- Electronics manufacturing
- Hospitals blood / Tissue banks
- Computer rooms
- Clean rooms
- Refrigerators
- Defense
- Other Critical areas.

Features:

- Complete environmental monitoring and alarm solution
- Wall-Mounted LED type for easy reading.
- Alarm set for Hi and Low limit-Temperature and Humidity.
- USB Datalogging Capacity 30,000 records
- Real-time data display.





21 Toh Guan Road East,
#09-01, Toh Guan Centre,
Singapore 608609.

sales@qsafe.com.sg

www.qsafe.com.sg

+65 8123 4812

